

TeltoCharge



 **ALPEV**



THE FUTURE OF CHARGING ON YOUR WALL

Easy, smart and reliable EV charger that you can customize to your needs. We offer an exceptional product that combines functionality, premium looks, high-quality build and smart EV charging features to save you time and money.

 **TELTONIKA**

TECHNICAL DATASHEET

A



DIMENSIONS



STANDARD FRONT PLATE OPTIONS



FRONT PLATE FINISH



B



OUTPUT OPTIONS



CONNECTIVITY TYPES



KEY BENEFITS



CUSTOMIZABLE

1 charger - 2 design options. Interchangeable front plates with two front plate options.



CONNECTED

Connect TeltoCharge to 3rd party OCPP Cloud platform via Wi-Fi/LAN/GSM. Or manage it with mobile device via Bluetooth.



COMPATIBLE

It is compatible with every electric vehicle and Plug-in (PHEV) hybrid now and in the future.



SECURE

Quick and easy EV charging authorization with NFC card or application, to prevent unwanted use.



CONVENIENT

Dynamic LED lights showing charging status, authentication and more



RELIABLE

TeltoCharge is IP55 and IK10 rated, meaning that it can withstand even the harshest outdoors weather.

DETAILED SPECIFICATIONS



CONNECTION POINT

- A** Tethered cable with Type 2 outlet (IEC 62196-2)
- B** Type 2 socket (IEC 62196-2)



CERTIFICATIONS

CE & UKCA compliant
Codes and standards:
EMC: 2014/53/EU, IEC 61851-21;
Safety: IEC/EN 61851-1;
Environment: 2011/65/EU, REACH, RoHS



WARRANTY

36 months



APPLICATION CONNECTIVITY

Bluetooth low energy Yes

CHARGER CONNECTIVITY

WiFi 2.4 GHz b/g/n connection Yes
Local management via APP Yes
NFC reader Yes
OCPP 1.6 Yes
Ethernet (RJ45) Yes
4G/LTE (CAT1), 3G, 2G (optional) Yes



PROJECTION

Output voltage and current monitoring Yes
Temperature monitoring Yes
Input voltage monitoring Yes
Residual current monitoring (30mA AC / 6 mA DC) Yes*
Standard: IEC62752:2016
Ground fault detection Yes
Degree of protection IP55
Impact resistant IK10
Fire class L94



TETHERED CABLE

Flame retardant rating UL-94V-0
Operating temperature -30°C - +50°C
Plug and play count 1000
Cable length 5 m / 7.5 m
IP rating IP54
Socket Type 2



CHARGING SPECIFICATION

Max 11kW
Up to 7.36kW at 32A 1 phase
Up to 11kW at 32A 3 phase
Dynamic configuration



NETWORK TYPE

T/N and IT/TT



VOLTAGE

Single phase: 230 V (±10%)
Three phase: 400 V (±10%)



MAIN FREQUENCY

50/60 Hz



OPERATING SPECIFICATIONS

Humidity to 95% RH non condensing;
-30°C - +50°C
Storage temperature -30°C - +50°C



TEMPERATURE SENSORS

In all main components



LED LIGHTS

LEDs showing the status of the charger



BUILT-IN ENERGY METER

Statistical data tracking Yes



LOAD BALANCING

Statistic load balancing Yes
Dynamic load balancing Yes
Phase balancing Yes
Solar energy support Yes



TELTOCHARGE PRODUCT CODES

ART.NO	DESCRIPTION
7011119002	Alp TeltoCharge, socket, 11 kW, Slate Grey
7011119502	Alp TeltoCharge, 5M cable, 11 kW, Slate Grey
7011119003	Alp TeltoCharge, socket, 11 kW, Accoya Wood
7011119503	Alp TeltoCharge, 5M cable, 11 kW, Accoya Wood
7030000014	Socket Alp TeltoCharge Single
7030000024	Socket Alp TeltoCharge Double
7030000095	Inepro PRO380-Mod MID 100A (TeltoCharge)

TELTONIKA ENERGY APP



Manage all your device settings from your mobile phone or tablet through the Teltonika Energy application.

- > Pair your EV charger with your phone through smart Teltonika Energy application via Bluetooth Low Energy connection.
- > Set up your device and get access to your consumption.
- > Monitor the status of your charger.
- > Schedule charging when the power is cheapest.
- > View your statistics in real time.
- > Set the charging current according to your needs.
- > Lock your charger to protect it from unwanted users & more...



Compatible with your device



TeltoCharge



Alp EV
Leursebaan 266,
4814 RE Breda,
The Netherlands



info@alp-ev.com
T +31 (0)85-246 5771

www.alp-ev.com